

## Toyota Alphard 10 (2002-2008)

MNH 10W	1MZ-FE	2WD	MZ, MS, MX
ANH 10W	2AZ-FE	2WD	AS, AX
MNH 15W	1MZ-FE	4WD	MZ, MS, MX
ANH 15W	2AZ-FE	4WD	AS, AX

System	Capacity (l)	Type
<b>Lubrication (w filter)</b>		
		<p>The chart shows three oil grade ranges: SAE 5W-20* (from -30 to 20°C), SAE 5W-30 (from -30 to 30°C), and SAE 10W-30 (from -10 to 40°C).</p>
1MZ-FE	4.7	API SL
2AZ-FE	4.3	API SL
<b>Cooling</b>		
1MZ-FE	11.0	
2AZ-FE	8.0	
<b>Automatic transmission</b>		
1MZ-FE WD	8.4	Toyota ATF Type T-IV
2AZ-FE 2WD	8.6	Toyota ATF Type T-IV
4WD	8.4	Toyota ATF Type T-IV
<b>Mechanical gearbox</b>		
<b>CVT</b>		
<b>Transfer</b>		
	0.4	Toyota Hypoid Gear Oil SX API GL-5 SAE 90
<b>Front differential</b>		
<b>Rear differential</b>		
	0.85	Toyota Hypoid Gear Oil SX API GL-5 SAE 90
<b>Power steering</b>		
	1.0	Toyota Power Steering Fluid
<b>Washer tank</b>		
	3.0	
<b>Fuel tank (RON)</b>		
2AZ-FE	70	"Regular" (91)
1MZ-FE	70	"Premium" (95)

Wheels	Disk	PCD	ET	Pressure (F/R)
205/65R16	16*6.5J	114.3*5	39	2.3
225/55R17	17*7J	114.3*5	45	2.3
T155/70D17	17*4T	114.3*5	40	4.2