

## Toyota Alphard / Vellfire 20 (2008-2015)

GGH20W	2GR-FE	3.5	2WD
GGH25W	2GR-FE	3.5	4WD
ANH20W	2AZ-FE	2.4	2WD
ANH25W	2AZ-FE	2.4	4WD

System	Capacity (l)	Type
<b>Lubrication (w filter)</b>		
2GR-FE		<p>SAE 10W-30 SAE 5W-30 SAE 5W-20*1</p>
2AZ-FE		<p>SAE 10W-30 SAE 5W-30 SAE 5W-20 SAE 0W-20*2</p>
2GR-FE	6.1	API SL..SM / GF-4
2AZ-FE	4.3	API SL..SM / GF-4
<b>Cooling</b>		
2GR-FE	10.6	
2AZ-FE	8.2	
<b>Automatic transmission</b>		
2GR-FE 2WD	6.5	Toyota ATF WS
2GR-FE 4WD	6.7	Toyota ATF WS
<b>CVT</b>		
2AZ-FE	8.7	Toyota CVT Fluid TC
<b>Transfer</b>		
	0.45	Toyota Hypoid Gear Oil SX API GL-5 SAE 85W-90
<b>Rear differential</b>		
	0.5	Toyota Hypoid Gear Oil SX API GL-5 SAE 85W-90
<b>Washer tank</b>		
	2.5	
<b>Fuel tank (RON)</b>		
2AZ-FE	65	"Regular" (91)
2GR-FE	65	"Premium" (95)

Wheels	Disk	PCD	ET	Pressure (F/R)
235/50R18 97V				2.4
215/60R17 96H				2.4
215/65R16 98H				2.4
T165/80R17 104M				4.2