

Toyota Alphard / Vellfire 30 (2015-)

AGH30W	2AR-FE	2.5	2WD
AGH35W	2AR-FE	2.5	4WD
GGH30W	2GR-FE	3.5	2WD
GGH35W	2GR-FE	3.5	4WD

System	Capacity (l)	Type
Lubrication (w filter)		
		<p>The chart shows four oil grades: SAE 10W-30, SAE 5W-30, SAE 5W-20, and SAE 0W-20*2. The temperature range is from -30 to 40 degrees Celsius. SAE 10W-30 is the top grade, followed by SAE 5W-30, SAE 5W-20, and SAE 0W-20*2 at the bottom.</p>
2AR-FE	4.4	API SN / ILSAC GF-5
2GR-FE	6.1	API SN / ILSAC GF-5
Cooling		
2AR-FE	8.8	
2GR-FE	10.6	
Automatic transmission		
2GR-FE (2WD/4WD)	6.5 / 6.7	Toyota ATF WS
CVT		
2AR-FE	7.3	Toyota CVT Fluid FE
Transfer		
	0.45	Toyota Diff. Gear Oil LT API GL-5 SAE 75W-85
Rear differential		
	0.5	Toyota Diff. Gear Oil LT API GL-5 SAE 75W-85
Washer tank		
	2.5	
Fuel tank (RON)		
2AR-FE (2WD/4WD)	75 / 65	"Regular" (91)
2GR-FE (2WD/4WD)	75 / 65	"Premium" (95)

Wheels	Disk	PCD	ET	Pressure (F/R)
235/50R18 97V	16*6.5J			2.4
215/60R17 99H	17*6.5J			2.4
215/65R16 98H	18*7.5J			2.4
T155/80D17 100M	17*4T			4.2