

Toyota Camry 40 (J) (2006-2011)

ACV40	2AZ-FE	2.4	2WD
ACV45	2AZ-FE	2.4	4WD

System	Capacity (l)	Type
Lubrication (w filter)		
		<p>The chart shows four oil grades: SAE 10W-30, SAE 5W-30, SAE 5W-20, and SAE 0W-20. The x-axis represents temperature in degrees Celsius, ranging from -30 to 40. SAE 10W-30 is suitable for temperatures above -10°C. SAE 5W-30 is suitable for temperatures above -25°C. SAE 5W-20 is suitable for temperatures above -30°C. SAE 0W-20 is suitable for temperatures above -35°C.</p>
2AZ-FE	4.3	API SL..SM / GF-4
Cooling		
2AZ-FE	6.2	
Automatic transmission		
2WD	8.0	Toyota ATF WS
4WD	8.1	Toyota ATF WS
CVT		
2AZ-FE	8.7	Toyota CVT Fluid TC
Transfer		
2006-	0.8	Toyota ATF WS
2008-	0.8	Toyota Hypoid Gear Oil SX API GL-5 SAE 85W-90
Rear differential		
	0,5	Toyota Hypoid Gear Oil SX API GL-5 SAE 85W-90
Power steering		
	1.0	Toyota Power Steering Fluid
Washer tank		
	4.5	
Fuel tank (RON)		
2WD	70	"Regular" (91)
4WD	65	"Regular" (91)

Wheels	Disk	PCD	ET	Pressure (F/R)
215/60R16 95H	16×6.5JJ	114.3×5	45	2.2
T155/70D17 110M	17×4T	114.3×5	40	4.2