

Toyota Celica 230 (J) (1999-2005)

ZZE230	1ZZ-FE	2WD	SS-I
ZZE231	2ZZ-GE	2WD	SS-II, SuperStrut

System	Capacity (l)	Type
Lubrication (w filter)		
		<p>The diagram shows a temperature scale from -30 to 40 degrees Celsius. Three oil grade indicators are shown: SAE 5W-20 (covering -30 to 40), SAE 5W-30 (covering -30 to 30), and SAE 10W-30 (covering 0 to 40).</p>
1ZZ-FE	3.7	API SL
2ZZ-GE	4.4	API SL
Cooling		
1ZZ-FE (MT/AT)	5.7 / 5.6	
2ZZ-GE (MT/AT)	5.9 / 5.8	
Automatic transmission		
1ZZ-FE	6.9	Toyota ATF Type T-IV
2ZZ-GE	7.6	Toyota ATF Type T-IV
Mechanical gearbox		
	1.95	Toyota Gear Oil Special API GL-3 SAE 75W-90
Power steering		
	0.9	Toyota Power Steering Fluid
Washer tank		
	4.5	
Fuel tank (RON)		
1ZZ-FE	55	"Regular" (91)
2ZZ-GE	55	"Premium" (95)

Wheels	Disk	PCD	ET	Pressure (F/R)
205/50R16 87V	16*6.5JJ	100*5	39	2.2
205/50R15 87V	15*6.5JJ	100*5	39	2.2
195/60R15 88H	26*6.5JJ	100*5	39	2.1
T135/70D16 100M	16*4T	100*5	39	4.2
T125/70D16 96M	16*4T	100*5	39	4.2