

**Crown 210 (2012-)**

GRS210	4GR-FSE	2.5	2WD
GRS211	4GR-FSE	2.5	4WD
GRS214	2GR-FSE	3.5	2WD
ARS210	8AR-FTS	2.0	2WD
AWS210	2AR-FSE + 1KM	2.5	2WD
GWS214	2GR-FXE	3.5	2WD

System	Capacity (l)	Type
<b>Lubrication (w filter)</b>		
		<p>The chart shows temperature points from -30 to 40. SAE 10W-30 is recommended for -30 to 30. SAE 5W-30 is recommended for -30 to 30. SAE 5W-20 is recommended for -30 to 20. SAE 0W-20*2 is recommended for -30 to 20.</p>
2GR-FSE, 4GR-FSE	6.4	API SN, RC / ILSAC GF-5
2GR-FXE	6.2	API SN, RC / ILSAC GF-5
2AR-FSE	4.5	API SN, RC / ILSAC GF-5
8AR-FTS	4.6	API SN, RC / ILSAC GF-5 (0W-20..5W-30)
<b>Cooling</b>		
2GR-FSE	9.8	
4GR-FSE	11.0	
2AR-FSE	8.2 / 2.2	(engine / hybrid power unit)
2GR-FXE	9.4 / 2.9	(engine / hybrid power unit)
8AR-FTS	8.0 / 3.1	(engine / intercooler)
<b>Automatic transmission</b>		
2GR-FSE 2WD	9.5	Toyota ATF WS
4GR-FSE 2WD	7.5	Toyota ATF WS
4GR-FSE 4WD	9.4	Toyota ATF WS
8AR-FTS	8.7	Toyota ATF WS
<b>Transmission</b>		
2AR-FSE	3.8	Toyota ATF WS
2GR-FXE	5.69	Toyota ATF WS
<b>Front differential</b>		
	0.7	Toyota Hypoid Gear Oil SX API GL-5 SAE 85W-90
<b>Rear differential</b>		
2GR-FSE	1.35	Toyota Diff. Gear Oil LT API GL-5 SAE 75W-85
4GR-FSE	1.15	Toyota Diff. Gear Oil LT API GL-5 SAE 75W-85
2AR-FSE	1.35	Toyota Diff. Gear Oil LT API GL-5 SAE 75W-85
2GR-FXE	1.35	Toyota Diff. Gear Oil LT API GL-5 SAE 75W-85
8AR-FTS	1.35	Toyota Diff. Gear Oil LT API GL-5 SAE 75W-85
<b>Washer tank</b>		
	4.7	
<b>Fuel tank (RON)</b>		
2GR-FSE	71	"Premium" (95)
2GR-FXE	65	"Premium" (95)
4GR-FSE	71	"Regular" (91)
2AR-FSE	65	"Regular" (91)
8AR-FTS	65	"Premium" (95)

Wheels	Disk	PCD	ET	Pressure (F/R)
215/60R16 95H	16×7J			2.5
215/55R17 94V	17×7J			2.3
225/50R17 94W	17×7.5J			2.4
225/45R18 91W	18×8J			2.3
T155/70D17 110M	17×4T			4.2