

Toyota Ipsum 20 (2001-2009)

ACM21W	2AZ-FE	2.4	2WD
ACM26W	2AZ-FE	2.4	4WD

System	Capacity (l)	Type
Lubrication (w filter)		
		<p>The chart shows temperature ranges in degrees Celsius: -30, -20, -10, 0, 10, 20, 30, 40. SAE 0W-20 is suitable for -30 to 20°C. SAE 5W-20 is suitable for -20 to 20°C. SAE 5W-30 is suitable for -10 to 30°C. SAE 10W-30 is suitable for 0 to 30°C.</p>
2AZ-FE	4.3	API SL..SM / GF-4
Cooling		
2AZ-FE	6.4 / 8.1	std / w rear heater
Automatic transmission		
2WD	8.6	Toyota ATF Type T-IV
4WD	8.7	Toyota ATF Type T-IV
Transfer		
	0.8	Toyota Hypoid Gear Oil SX API GL-5 SAE 85W-90
Rear differential		
	0.5	Toyota Hypoid Gear Oil SX API GL-5 SAE 85W-90
Power steering		
	1.0	Toyota Power Steering Fluid
Washer tank		
	2.5 / 4.5	std / cold area
Fuel tank (RON)		
	60	"Regular" (91)

Wheels	Disk	PCD	ET	Pressure (F/R)
205/65R15 94S	15*6.5JJ	114.3×5	45	2.3
205/60R16 92H	16*6.5JJ	114.3×5	45	2.3
215/50R17 91V	17*6.5JJ	114.3×5	45	2.3
T135/80D16 101M	16*4T	114.3×5	50	4.2