

Toyota Kluger (2000-2007)

MCU20W	1MZ-FE	3.0	2WD
MCU25W	1MZ-FE	3.0	4WD
ACU20W	2AZ-FE	2.4	2WD
ACU25W	2AZ-FE	2.4	4WD

System	Capacity (l)	Type
Lubrication (w filter)		
		<p>The chart shows three oil grades: SAE 5W-20* (marked with an asterisk), SAE 5W-30, and SAE 10W-30. The temperature scale ranges from -30 to 40 degrees Celsius.</p>
1MZ-FE	4.7	API SL
2AZ-FE	4.3	API SL
Cooling		
1MZ-FE	9.0 / 10.8	(w/o rear heater / w rear heater)
2AZ-FE	6.4 / 7.8	(w/o rear heater / w rear heater)
Automatic transmission		
1MZ-FE 2WD	8.8	Toyota ATF Type T-IV
2AZ-FE 2WD	8.6	Toyota ATF Type T-IV
1MZ-FE 4WD	9.0	Toyota ATF Type T-IV
2AZ-FE 4WD	8.7	Toyota ATF Type T-IV
Transfer		
1MZ-FE	0.9	Toyota Hypoid Gear Oil SX API GL-5 SAE 85W-90
2AZ-FE	0.9	Toyota Hypoid Gear Oil SX API GL-5 SAE 85W-90
Rear differential		
	0.9	Toyota Hypoid Gear Oil SX API GL-5 SAE 90
Power steering		
1MZ-FE	0.9	Toyota Power Steering Fluid
2AZ-FE	0.8	Toyota Power Steering Fluid
Washer tank		
	4.5	
Fuel tank (RON)		
1MZ-FE	72	"Premium" (95)
2AZ-FE	72	"Regular" (91)

Wheels	Disk	PCD	ET	Pressure (F/R)
225/65R17 99H	17×6.5JJ	114.3×5	35	2.1
215/70R16 99S	16×6.5JJ	114.3×5	35	2.1
T165/80R17 104M	17×4T	114.3×5	40	4.2