

Toyota Mark X 130 (2009-)

GRX130	4GR-FSE	2.5	2WD
GRX135	4GR-FSE	2.5	4WD
GRX133	2GR-FSE	3.5	2WD

System	Capacity (l)	Type
Lubrication (w filter)		
		<p>The diagram shows a temperature scale from -30 to 40. Four oil grade indicators are shown as arrows pointing right: SAE 10W-30 (range -30 to 40), SAE 5W-30 (range -20 to 40), SAE 5W-20 (range -10 to 40), and SAE 0W-20 (range 0 to 40).</p>
2WD	6.3	API SL..SN / ILSAC GF-4..5
4WD	6.4	API SL..SN / ILSAC GF-4..5
Cooling		
2GR-FSE	9.2	
4GR-FSE	9.4	
Automatic transmission		
2GR-FSE 2WD	7.9	Toyota ATF WS
4GR-FSE 2WD	7.5	Toyota ATF WS
4GR-FSE 4WD	9.4	Toyota ATF WS
Front differential		
	0.7	Toyota Hypoid Gear Oil SX API GL-5 SAE 85W-90
Rear differential		
2GR-FSE	1.35	Toyota Diff.Gear Oil LT API GL-5 SAE 75W-85
4GR-FSE	1.15	Toyota Diff.Gear Oil LT API GL-5 SAE 75W-85
Washer tank		
	4.7	
Fuel tank (RON)		
4GR-FSE	71	"Regular" (91)
2GR-FSE	71	"Premium" (95)

Wheels	Disk	PCD	ET	Pressure (F/R)
215/60R16 95H	16×7J			2.5
235/45R18 94W	18×8J			2.4
235/40R19 92Y	19×8J			2.4
T155/70D17 110M	17×4T			4.2