

Toyota Opa (2000-2005)

ZCT10	1ZZ-FE	2WD	
ZCT15	1ZZ-FE	4WD	
ACT15	1AZ-FSE	2WD	

System	Capacity (l)	Type
Lubrication (w filter)		
		<p>The chart shows three oil grades: SAE 5W-20 (top), SAE 5W-30 (middle), and SAE 10W-30 (bottom). The temperature scale ranges from -30 to 40 degrees Celsius with major ticks every 10 units.</p>
1ZZ-FE	3.7	API SL
1AZ-FSE	4.2	API SL
Cooling		
1ZZ-FE	6.1	
1AZ-FSE	5.8	
Automatic transmission		
1ZZ-FE	6.9	Toyota ATF Type T-IV
CVT		
1AZ-FSE	8.4	Toyota CVT Fluid TC
Transfer		
	0.9	Toyota Gear Oil Super API GL-5 SAE 75W-90
Rear differential		
	0.5	Toyota Hypoid Gear Oil SX API GL-5 SAE 85W-90
Power steering		
	0.8	Toyota Power Steering Fluid
Washer tank		
	3.5	
Fuel tank (RON)		
	60	"Regular" (91)

Wheels	Disk	PCD	ET	Pressure (F/R)
195/65R15 91S	15×6JJ	100*5	45	2.1-2.2 / 1.9-2.0
185/70R14 88S	14*6JJ	100*5	45	2.2 / 2.0
T135/80D16 101M	16×4T	100*5	42	4.2
T125/70D16 96M	16×4T	100*5	42	4.2