

## Toyota Allion / Premio 240 (2001-2007)

NZT240	1NZ-FE	2WD	
ZZT240	1ZZ-FE	2WD	
ZZT245	1ZZ-FE	4WD	
AZT240	1AZ-FSE	2WD	

System	Capacity (l)	Type
<b>Lubrication (w filter)</b>		
		<p>The diagram shows a temperature scale from -30 to 40 degrees Celsius. Four oil grade ranges are indicated by arrows pointing to the right:</p> <ul style="list-style-type: none"> <li>SAE 0W-20: covers from -30 to 20</li> <li>SAE 5W-20: covers from -20 to 20</li> <li>SAE 5W-30: covers from -10 to 30</li> <li>SAE 10W-30: covers from 0 to 30</li> </ul>
1NZ-FE	3.7	API SL
1ZZ-FE	3.7	API SL
1AZ-FSE	4.2	API SL
<b>Cooling</b>		
1NZ-FE	6.3	
1ZZ-FE (2WD/4WD)	6.9 / 6.5	
1AZ-FSE	7.0	
<b>Automatic transmission</b>		
1NZ-FE	6.85	Toyota ATF Type T-IV
1ZZ-FE	6.88	Toyota ATF Type T-IV
<b>CVT</b>		
1AZ-FSE	5.6	Toyota CVT Fluid TC
<b>Transfer</b>		
	0.9	Toyota Gear Oil Super API GL-5 SAE 75W-90
<b>Rear differential</b>		
	0.5	Toyota Hypoid Gear Oil SX API GL-5 SAE 85W-90
<b>Power steering</b>		
	0.8	Toyota Power Steering Fluid
<b>Washer tank</b>		
	3.5	
<b>Fuel tank (RON)</b>		
	60	"Regular" (91)

Wheels	Disk	PCD	ET	Pressure (F/R)
195/65R15 91S (2WD)	15×6JJ	100*5	45	2.3 / 2.0
195/65R15 91S (4WD)	15×6JJ	100*5	45	2.2 / 1.9
185/70R14 88S	14×6JJ	100*5	45	2.1
T125/70D16 96M	16×4T	100*5	42	4.2
T135/80D16 101M	16×4T	100*5	42	4.2