

Toyota TownAce / LiteAce S400 (2008-)

S402M	3SZ-VE	1.5	2WD
S412M			4WD
S402U			2WD
S412U			4WD

System	Capacity (l)	Type
Lubrication (w filter)		
3SZ-VE	3.5	API SN / ILSAC GF-5
Cooling		
	6.7 / 6.55	w/o rear heater (MT / AT)
	7.6 / 7.45	w rear heater (MT / AT)
Transmission (AT)		
Gearbox	4.8	Toyota ATF Type T-IV
Transfer	1.6	Toyota MG Gear Oil Spec.II API GL-3 SAE 75W-90
Transmission (MT)		
Gearbox (2WD)	1.1	Toyota MG Gear Oil Spec.II API GL-3 SAE 75W-90
Gearbox/Transfer(4WD)	2.4	Toyota MG Gear Oil Spec.II API GL-3 SAE 75W-90
Front differential		
	0.47	Toyota Hypoid Gear Oil SX API GL-5 SAE 85W-90
Rear differential		
	2.35	Toyota Hypoid Gear Oil SX API GL-5 SAE 85W-90
Washer tank		
	2.0	
Fuel tank (RON)		
	43	"Regular" (91)

Wheels	Disk	PCD	ET	Pressure (F/R)
165R13 8PR (Van)	13×5J			2.2 / 2.6
175R13 8PR (Truck)	13×5J			2.2 / 2.6