

Toyota Will VS (2001-2004)

ZZE128	2ZZ-GE	2WD	
ZZE127	1ZZ-FE	2WD	
ZZE129	1ZZ-FE	4WD	
NZE127	1NZ-FE	2WD	

System	Capacity (l)	Type
Lubrication (w filter)		
		<p>The chart shows three oil grades: SAE 5W-20 (top), SAE 5W-30 (middle), and SAE 10W-30 (bottom). The x-axis represents temperature in degrees Celsius, ranging from -30 to 40. SAE 5W-20 is suitable for temperatures down to -30°C. SAE 5W-30 is suitable for temperatures down to -20°C. SAE 10W-30 is suitable for temperatures down to -10°C.</p>
1NZ-FE	3.7	API SJ, SL
1ZZ-FE	3.7	API SJ, SL
2ZZ-GE	4.4	API SJ, SL
Cooling		
1NZ-FE	5.9	
1ZZ-FE	6.5	
2ZZ-GE	6.7	
Automatic transmission		
1NZ-FE	6.85	Toyota ATF Type T-IV
1ZZ-FE	6.9	Toyota ATF Type T-IV
2ZZ-GE	7.6	Toyota ATF Type T-IV
Mechanical gearbox		
	2.3	Toyota MG Gear Oil Special-II GL-3 SAE75W-90
Transfer		
	0.9	Toyota Gear Oil Super GL-5 SAE75W-90
Rear differential		
	0.6	Toyota Hypoid Gear Oil SX API GL-5 SAE85W-90
Power steering		
	0.7	Toyota Power Steering Fluid
Washer tank		
	2.5	
Fuel tank (RON)		
1NZ-FE, 1ZZ-FE	50	"Regular" (91)
2ZZ-GE	50	"Premium" (95)