

Toyota Allion / Premio 260 (2007-)

NZT260	1NZ-FE	1.5i	2WD
ZRT260 2007-2010	2ZR-FE	1.8i	2WD
ZRT265 2007-2010	2ZR-FE	1.8i	4WD
ZRT260 2010-	2ZR-FAE	1.8i	2WD
ZRT265 2010-	2ZR-FAE	1.8i	4WD
ZRT261	3ZR-FAE	2.0i	2WD

System	Capacity (l)	Type
Lubrication (w filter)		
		<p>The chart shows four recommended SAE grades: SAE 10W-30 (top), SAE 5W-30, SAE 5W-20, and SAE 0W-20* (bottom). The x-axis represents temperature in degrees Celsius, ranging from -30 to 40.</p>
1NZ-FE	3.7	API SL..SN / GF-4..5
2ZR-FE	4.2	API SL..SN / GF-4..5
2ZR-FAE	4.2	API SL..SN / GF-4..5
3ZR-FAE	4.2	API SL..SN / GF-4..5
Cooling		
1NZ-FE	5.3	
2ZR-FE	5.4	
2ZR-FAE	5.4	
3ZR-FAE	5.4	
CVT		
1NZ-FE 2007-2013	8.09	Toyota CVT Fluid TC
1NZ-FE 2013-	7.50	Toyota CVT Fluid FE
2ZR-FE 2WD	8.11	Toyota CVT Fluid TC
2ZR-FE 4WD	7.98	Toyota CVT Fluid TC
2ZR-FAE 2WD -2013	8.11	Toyota CVT Fluid TC
2ZR-FAE 4WD -2013	7.98	Toyota CVT Fluid TC
2ZR-FAE 2WD 2013-	8.00	Toyota CVT Fluid FE
2ZR-FAE 4WD 2013-	7.90	Toyota CVT Fluid FE
3ZR-FAE 2007-2014	8.70	Toyota CVT Fluid TC
3ZR-FAE 2014-	8.70	Toyota CVT Fluid FE
Transfer		
	0.9	Toyota Gear Oil Super API GL-5 SAE 75W-90
Rear differential		
2007-2015	0.5	Toyota Hypoid Gear Oil SX API GL-5 SAE 85W-90
2015-	0.5	Toyota Diff. Gear Oil LT API GL-5 SAE 75W-85
Washer tank		
	2.5	
Fuel tank (RON)		
	60	"Regular" (91)

Wheels	Disk	PCD	ET	Pressure (F/R)
185/70R14 88S				2.3/2.0
185/65R15 88S	15×6J			2.3/2.3
195/65R15 91S	15×6J			2.3/2.3
195/55R16 86V	16×6J			2.2/2.0
T125/70D16 96M	16×4T			4.2
T135/80D16 101M	16×4T			4.2