

Toyota Alphard / Vellfire 30 (2015-)

AGH30W	2AR-FE	2.5i	2WD
AGH35W	2AR-FE	2.5i	4WD
GGH30W -2017.12	2GR-FE	3.5i	2WD
GGH35W -2017.12	2GR-FE	3.5i	4WD
GGH30W 2017.12-	2GR-FKS	3.5i	2WD
GGH35W 2017.12-	2GR-FKS	3.5i	4WD

System	Capacity (l)	Type
Lubrication (w filter)		
<p>2AR-FE, 2GR-FE</p>		<p>2GR-FKS</p>
2AR-FE	4.4	API SN,RC / ILSAC GF-5
2GR-FE	6.1	API SN,RC / ILSAC GF-5
2GR-FKS	5.4	API SN,RC / ILSAC GF-5
Cooling		
2AR-FE	8.8 / 9.3	-2017.12 / 2017.12-
2GR-FE	10.6	
2GR-FKS	10.7	
Automatic transmission		
2GR-FE (2WD/4WD)	6.5 / 6.7	Toyota ATF WS
2GR-FKS	7.5	Toyota ATF WS
CVT		
2AR-FE	7.3-7.5	Toyota CVT Fluid FE
Transfer		
	0.45	Toyota Diff. Gear Oil LT API GL-5 SAE 75W-85
Rear differential		
	0.5	Toyota Diff. Gear Oil LT API GL-5 SAE 75W-85
Washer tank		
	2.5	
Fuel tank (RON)		
2AR-FE (2WD/4WD)	75 / 65	"Regular" (91)
2GR-FE (2WD/4WD)	75 / 65	"Premium" (95)
2GR-FKS (2WD/4WD)	75 / 65	"Premium" (95)

Wheels	Disk	PCD	ET	Pressure (F/R)
215/65R16 98H	16*6.5J			2.4
225/60R17 99H	17*6.5J			2.4
235/50R18 97V	18*7.5J			2.4
T155/80D17 100M	17*4T			4.2