

**Toyota Probox / Succeed 160 (2014-)**

NSP160V	1NR-FE	1.3i	2WD
NCP160V	1NZ-FE	1.5i	2WD
NCP165V	1NZ-FE	1.5i	4WD

System	Capacity (l)	Type
<b>Lubrication (w filter)</b>		
		<p>The chart shows four oil grades: SAE 10W-30, SAE 5W-30, SAE 5W-20, and SAE 0W-20. The temperature scale ranges from -30 to 40 degrees Celsius. SAE 10W-30 is the top-most grade, followed by SAE 5W-30, SAE 5W-20, and SAE 0W-20 at the bottom.</p>
1NZ-FE	3.7	API SN, RC / ILSAC GF-5
1NR-FE	3.4	API SN, RC / ILSAC GF-5
<b>Cooling</b>		
1NZ-FE	5.0	
1NR-FE	4.7	
<b>CVT</b>		
1NZ-FE 2WD	7.47	Toyota CVT Fluid FE
1NZ-FE 4WD	7.88	Toyota CVT Fluid FE
1NR-FE	6.42	Toyota CVT Fluid FE
<b>Transfer</b>		
	0.45	Toyota Hypoid Gear Oil SX API GL-5 SAE 85W-90
<b>Rear differential</b>		
	1.7	Toyota Hypoid Gear Oil SX API GL-5 SAE 85W-90
<b>Washer tank</b>		
	2.3	
<b>Fuel tank (RON)</b>		
	50	"Regular" (91)

Wheels	Disk	PCD	ET	Pressure (F/R)
155/80R14 88/86N LT	14×5J			2.2-2.4 / 2.2-2.9