

Toyota Probox / Succeed 50 (2002-2014)

NCP58G	1NZ-FE	1.5	2WD
NCP59G	1NZ-FE	1.5	4WD
NCP50V	2NZ-FE	1.3	2WD
NCP51V	1NZ-FE	1.5	2WD
NCP52V	1NZ-FNE	1.5	2WD
NCP55V	1NZ-FE	1.5	4WD

System	Capacity (l)	Type
Lubrication system (w filter)		
		<p>The chart shows four oil grades: SAE 10W-30, SAE 5W-30, SAE 5W-20, and SAE 0W-20. The temperature scale ranges from -30 to 40 degrees Celsius. SAE 10W-30 is the top-most grade, followed by SAE 5W-30, SAE 5W-20, and SAE 0W-20 at the bottom.</p>
1NZ-FE	3.7	API SL..SM / GF-4
2NZ-FE	3.7	API SL..SM / GF-4
Cooling system		
1NZ-FE (MT/AT)	4.4/4.3	
2NZ-FE (MT/AT)	4.5/4.4	
Automatic transmission		
1NZ-FE 2WD	6.8	Toyota ATF Type T-IV
1NZ-FE 4WD	6.9	Toyota ATF Type T-IV
2NZ-FE	5.6	Toyota ATF Type T-IV
Mechanical gearbox		
2NZ-FE	1.9	Toyota MG Gear Oil Spec.II API GL-3 SAE 75W-90
1NZ-FE	1.9	Toyota MG Gear Oil Spec.II API GL-3 SAE 75W-90
Transfer		
	0.9	Toyota Gear Oil Super API GL-5 SAE 75W-90
Rear differential		
	1.7	Toyota Hypoid Gear Oil SX API GL-5 SAE 85W-90
Power steering		
	0.7	Toyota Power Steering Fluid
Washer tank		
	2.0	
Fuel tank (RON)		
	50	"Regular" (91)

Wheels	Disk	PCD	ET	Pressure (F/R)
165R13 6PRLT	13×5J	100×4	39	2.2
165/80R13 83S	13×5J	100×4	39	2.1