

Toyota Progres (1998-2007)

JCG10	1JZ-FSE	2WD	NC250
JCG15	1JZ-FSE	4WD	NC250Four
JCG11	2JZ-FSE	2WD	NC300

System	Capacity (l)	Type
Lubrication (w filter)		
		<p>The chart shows three oil grades: SAE 10W-30 (top), SAE 5W-30 (middle), and SAE 5W-20*1 (bottom). The x-axis represents temperature in degrees Celsius, ranging from -30 to 40. SAE 10W-30 is suitable for temperatures from -30 to 30. SAE 5W-30 is suitable from -30 to 40. SAE 5W-20*1 is suitable from -30 to 30.</p>
2WD	5.4	API SL
4WD	4.5	API SL
Cooling		
1JZ-FSE	6.9	
2JZ-FSE	7.5	
Automatic transmission		
1JZ-FSE 2WD	7.4	Toyota ATF Type T-IV
1JZ-FSE 4WD	8.7	Toyota ATF Type T-IV
2JZ-FSE	8.2	Toyota ATF Type T-IV
Front differential		
	0.7	Toyota Hypoid Gear Oil SX API GL-5 SAE 85W-90
Rear differential		
1JZ-FSE	1.00	Toyota Hypoid Gear Oil SX API GL-5 SAE 85W-90
2JZ-FSE	1.15	Toyota Hypoid Gear Oil SX API GL-5 SAE 85W-90
Power steering		
2WD	0.8	Toyota Power Steering Fluid
4WD	0.9	Toyota Power Steering Fluid
Washer tank		
	3.5	
Fuel tank (RON)		
	70	"Premium" (95)