

Toyota RAV4 30 (J) (2006-)

ACA31W	2AZ-FE	2.4	4WD
ACA36W	2AZ-FE	2.4	2WD

System	Capacity (l)	Type
Lubrication (w filter)		
		<p>The chart shows temperature ranges in degrees Celsius: -30, -20, -10, 0, 10, 20, 30, 40. SAE 0W-20 covers -30 to 40. SAE 5W-20 covers -20 to 40. SAE 5W-30 covers -10 to 40. SAE 10W-30 covers 0 to 40.</p>
2AZ-FE	4.3	API SL..SN / ILSAC GF-4..5
Cooling		
2AZ-FE	6.2	
CVT		
	8.4	Toyota CVT Fluid TC / FE
Transfer		
	0.45	Toyota Hypoid Gear Oil SX API GL-5 SAE 85W-90
Rear differential		
	0.5	Toyota Hypoid Gear Oil SX API GL-5 SAE 85W-90
Washer tank		
	4.8 / 2.5	cold area / std
Fuel tank (RON)		
	60	"Regular" (91)

Wheels	Disk	PCD	ET	Pressure (F/R)
225/65R17 101H	17×6.5-7JJ	114.3×5	45	2.2
235/55R18 99H	18×7.5J	114.3×5	39	2.2