

**Toyota Voltz (2002-2004)**

ZZE136	1ZZ-FE	2WD	S
ZZE138	1ZZ-FE	4WD	S
ZZE137	2ZZ-GE	2WD	Z

System	Capacity (l)	Type
<b>Lubrication (w filter)</b>		
		<p>The chart shows three oil grades: SAE 5W-20 (top), SAE 5W-30 (middle), and SAE 10W-30 (bottom). The x-axis represents temperature in degrees Celsius, ranging from -30 to 40. SAE 5W-20 is suitable for temperatures down to -30°C. SAE 5W-30 is suitable for temperatures down to -20°C. SAE 10W-30 is suitable for temperatures down to -10°C.</p>
1ZZ-FE	3.7	API SJ, SL
2ZZ-GE	4.4	API SJ, SL
<b>Cooling</b>		
1ZZ-FE	6.5	
2ZZ-GE	6.7	
<b>Automatic transmission</b>		
1ZZ-FE (2WD / 4WD)	7.2 / 6.9	Toyota ATF Type T-IV
2ZZ-GE	7.6	Toyota ATF Type T-IV
<b>Transfer</b>		
	0.9	Toyota Gear Oil Super GL-5 SAE75W-90
<b>Rear differential</b>		
	0.5	Toyota Hypoid Gear Oil SX API GL-5 SAE85W-90
<b>Power steering</b>		
	0.7	Toyota Power Steering Fluid
<b>Washer tank</b>		
	4.5	
<b>Fuel tank (RON)</b>		
1ZZ-FE (2WD/4WD)	50 / 45	"Regular" (91)
2ZZ-GE	50	"Premium" (95)

Wheels	Disk	PCD	ET	Pressure (F/R)
205/55R16 89V	16*6,5JJ	100*5	39	2,2 (2WD) 2,4 / 2,2 (4WD)
215/50R17 91V	17*7JJ	100*5	45	2,2
T135/70R16 100M	16*4T	100*5	45	4,2
T135/80R16 100M	16*4T	100*5	45	4,2